

IFW/AF

PTO/SB/21 (09-04)

Approved for use through 07/31/2006. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## TRANSMITTAL FORM

(to be used for all correspondence after initial filing)

Total Number of Pages in This Submission

13

Application Number

10/618,232

Filing Date

07/14/03

First Named Inventor

Fetterolf et al

Art Unit

3617

Examiner Name

Robert J. McCarry

Attorney Docket Number

6235

### ENCLOSURES (Check all that apply)

<input type="checkbox"/> Fee Transmittal Form	<input type="checkbox"/> Drawing(s)	<input type="checkbox"/> After Allowance Communication to TC
<input type="checkbox"/> Fee Attached	<input type="checkbox"/> Licensing-related Papers	<input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences
<input type="checkbox"/> Amendment/Reply	<input type="checkbox"/> Petition	<input checked="" type="checkbox"/> Appeal Communication to TC (Appeal Notice, Brief, Reply Brief)
<input type="checkbox"/> After Final	<input type="checkbox"/> Petition to Convert to a Provisional Application	<input type="checkbox"/> Proprietary Information
<input type="checkbox"/> Affidavits/declaration(s)	<input type="checkbox"/> Power of Attorney, Revocation Change of Correspondence Address	<input type="checkbox"/> Status Letter
<input type="checkbox"/> Extension of Time Request	<input type="checkbox"/> Terminal Disclaimer	<input checked="" type="checkbox"/> Other Enclosure(s) (please identify below):
<input type="checkbox"/> Express Abandonment Request	<input type="checkbox"/> Request for Refund	Return Postcard and Check No. 004083
<input type="checkbox"/> Information Disclosure Statement	<input type="checkbox"/> CD, Number of CD(s) _____	
<input type="checkbox"/> Certified Copy of Priority Document(s)	<input type="checkbox"/> Landscape Table on CD	
<input type="checkbox"/> Reply to Missing Parts/Incomplete Application	Remarks	
<input type="checkbox"/> Reply to Missing Parts under 37 CFR 1.52 or 1.53		

### SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT

Firm Name	AMSTED Industries, Inc.		
Signature			
Printed name	Edward J. Brosius		
Date	05/04/05	Reg. No.	28,695

### CERTIFICATE OF TRANSMISSION/MAILING

I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below:

Signature			
Typed or printed name	Edward J. Brosius	Date	05/04/05

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.



Case No. 6235-Fetterolf et al.

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Applicants: Fetterolf et al. )

Serial No.: 10/618,232 )

Filed: July 14, 2003 )

For: LOCOMOTIVE DRAFT GEAR )  
ASSEMBLY AND YOKE )

Examiner: McCarry, R. J.

Group Art Unit: 3617

**APPEAL BRIEF**

Commissioner of Patents  
Po Box 1450  
Alexandria, VA 22313-1450

**CERTIFICATE OF MAILING**

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231 on May 4, 2005.

Applicant's Attorney: Edward J. Brosius

Signature E J Brosius

Date May 4, 2005

Dear Sir:

The following Appeal Brief is submitted in triplicate to complete the Notice of Appeal filed on March 24, 2005.

**1. Real Party in Interest**

The real party in interest are the applicants, J. F. Fetterolf, et al.  
ASF - Keystone Incorporated is the assignee of all such applicants.

**2. Related Appeals and Interferences**

None.

**3. Status of Claims**

Claims 1-12 are currently pending and are under final rejection dated January 12, 2005.

The final rejection of claims 1-12 is appealed.

Accordingly, claims 1-12 are on appeal.

4. Status of amendments

No amendments were filed subsequent to the final rejection.

5. Summary of claimed subject matter

The claims as presently pending were amended in an amendment dated October 19, 2004, wherein claims 13-25 were cancelled.

The present invention relates to a draft gear cushioning assembly for use in a locomotive draft sill-coupler assembly.

In the detailed description of the invention, like reference numbers are used for like parts.

Claims 1-12 read as follows, with only reference numerals added for ready relation to the drawings.

Claim 1

(original): A yoke (10) for use in a railway locomotive draft gear assembly, the yoke comprising:

a front wall (18), a back wall (16), a top strap (12) extending from the front wall to the back wall, a bottom strap (14) extending from the front wall to the back wall,

the front wall (18) comprising two side sections (28), each side section extending vertically between the top strap (12) and the bottom strap (14), the front wall comprising a bottom section (24), a center section (26) and a top section (22), each of the bottom, center and the top sections having a convex edge and extending laterally between the two side sections,

the top strap (12) of reduced width extending from the front wall to the back wall, the bottom strap (14) of reduced width extending from the front wall to the back wall, and the back wall (16) includes at least one indented section (40) of reduced thickness extending from near the top strap to near the bottom strap.

Claim 2

(original): The yoke (10) of claim 1 further comprising,

an indented area of reduced thickness in the top strap (12) and an indented area (32) of reduced thickness in the bottom strap (14).

Claim 3

(original): The yoke (10) of claim 1,  
where in the back wall (16) includes an inside facing surface (17) forming a bearing area.

Claim 4

(original): The yoke of claim 1,  
wherein the width of the top strap (12) is about 8.25 inches,  
the width of the bottom strap (14) is about 8.25 inches  
and the width of the back wall (16) is about 8.25 inches.

Claim 5

(original): A draft gear assembly for use in a railway locomotive coupling assembly, the draft gear assembly comprising:  
a yoke (10) comprising:  
a front wall (18), a back wall (16), a top strap (12) extending from the front wall to the back wall, a bottom strap (14) extending from the front wall to the back wall, the front wall (18) comprising two side sections (28), each side section extending vertically between the top strap (12) and the bottom strap (14), the front wall (18) further comprising a bottom section (24), a center section (26) and a top section (22), each of the bottom, center and top sections having a laterally convex shape and extending laterally between the two side sections,  
the top strap (12) of reduced width extending from the front wall to the back wall,

the bottom strap (14) of reduced width extending from the front wall to the back wall,  
and back wall (16) includes at least one indented section (40) of reduced thickness extending from near the top strap to near the bottom strap,  
a front coupler follower (52) positioned between the top strap and the bottom strap and adjacent an internal surface of the front wall,  
a rear coupler follower (54) positioned between the top strap and the bottom strap and adjacent an internal surface of the back wall,  
and a resilient draft gear (56) located between the front and rear coupler followers.

Claim 6

(original): The draft gear assembly of claim 5,  
wherein the yoke to strap (12) includes an indented area of reduced thickness,  
and the yoke bottom strap (14) includes an indented area of reduced thickness.

Claim 7

(original): The draft gear assembly of claim 5,  
Wherein an inside facing surface (17) of the back wall forms a bearing area.

Claim 8

(original): The draft gear assembly of claim 5,  
wherein the width of the top strap (12) is about 8.25 inches,  
the width of the bottom strap (14) is about 8.25 inches  
and the width of the back wall (16) is about 8.25 inches.

Claim 9

(original): The draft gear assembly of claim 5,  
wherein the front coupler follower (52) comprises a generally rectangular structure having a top edge, a bottom edge, two laterally spaced side edges, a front face and rear face,  
and each side edge having a side support structure (53) extending longitudinally from the rear face, each side edge support structure having a lightener opening (59) therein.

Claim 10

(original): The draft gear assembly of claim 5,  
wherein the front coupler follower (52) comprises a generally rectangular structure having a top edge, a bottom edge and two laterally spaced side edges,  
and a center support structure (55) extending longitudinally from the rear face,  
the center support structure having lightener areas (57) at each corner.

Claim 11

(original): The draft gear assembly of claim 5,  
wherein the rear coupler follower (54) comprises a generally rectangular structure having a top edge, a bottom edge, two laterally spaced side edges, a front face and a rear face, and each side edge having a side support structure (53) extending longitudinally from the rear face, each side edge support structure having a lightener opening (59) therein.

Claim 12

(original): The draft gear assembly of claim 5,

wherein the rear coupler follower (54) comprises a generally rectangular structure having a top edge,  
a bottom edge and two laterally spaced side edges,  
and a center support structure (55) extending longitudinally from the rear face, the center support structure having lightener areas (57) at each corner.

6. Grounds of rejection to be reviewed on appeal.

The following issues are presented for review.

For claims 1-3, whether these claims as presently pending, are unpatentable under 35 USC 102(b) over US Patent No. 5,305,899, Kaufhold et al.

For claims 4-12, whether these claims as presently pending, are unpatentable under 35 USC 103(a) over Kaufhold in view of US Patent No. 6,446,820, Barker et al.

7. Argument.

Claims 1-12 are under appeal. Claims 1-3 have been rejected as unpatentable in the final rejection of January 12, 2005 under 35 USC 102(b) as being anticipated by Kaufhold and claims 4-12 as unpatentable under 35 USC 103(a) over Kaufhold, et al in view of Barker et al.

In simplified language, Claim 1 sets forth a yoke (10) for use in railway locomotive draft gear assembly, the yoke including  
a front wall (18), a back wall (16), a top strap (12) extending from the front wall to the back wall, and a bottom strap (14),

the front wall further comprising a bottom section (24), a center section (26) and a top section (12), each of which has extending laterally between the two side sections,

the top strap (12) is of reduced width extending from the front wall to the back wall, the bottom strap (14) is of reduced width extending from the front wall to the back wall, and the back wall (16) includes at least one indented section (40) of reduced thickness extending from near the top strap to near the bottom strap.

In simplified language, Claim 5 sets forth a draft gear assembly for use in a railway locomotive coupling assembly comprising a yoke (10) including a front wall (18), a back wall (16), a top strap (12) extending from the front wall to the back wall, a bottom strap (14) extending from the front wall to the back wall, the front wall (18) comprising two side sections (28), each side section extending vertically between the top strap (12) and the bottom strap (14), the front wall (18) further has a bottom section (24), a center section (26) and a top section (22), each of which extending laterally between the two side sections,

the top strap (12) is of reduced width extending from the front wall to the back wall,

the bottom strap (14) is of reduced width extending from the front wall to the back wall, and the back wall (16) includes at least one indented section (40) of reduced thickness extending from near the top strap to near the bottom strap,



a front coupler follower (52) is positioned between the top strap and the bottom strap and adjacent an internal surface of the front wall,

a rear coupler follower (54) is positioned between the top strap and the bottom strap and adjacent an internal surface of the back wall,

and a resilient draft gear (56) is located between the front and rear coupler followers.

The rejection of claims 1-3 (possibly this was meant to be claims 1-4) under 35 USC 102(b) over Kaufhold is not readily understood. The Examiner essentially repeats the prior non-final rejection and fails to take into account that in claim 1, the front wall of the yoke comprises a bottom section, a center section and a top section, each extending between two side sections. Kaufhold does not disclose any such center section.

Similarly, the rejection of claims 4-12 under 35 USC 103(a) over Kaufhold in view of Barker et al is not readily understood. Barker et al is said to disclose a resilient draft gear between coupler followers. Again, the Examiner fails to take into account that in claim 5, the front wall of the yoke comprises a bottom section, a center section and a top section, each extending between two side sections. Barker et al does not disclose or obviate any such center section.

A review of the disclosure of Kaufhold and Barker et al appears in order.

The Examiner has rejected claims 1-3 under 35 USC 102(b) as anticipated by U.S. Patent No. 5,305,899, Kaufhold. Claim 1 sets forth that the front wall of the yoke comprises a bottom section, a center section and top section, each having a convex edge and extending between two side sections.

Kaufhold discloses a yoke 120 having front side walls 134 and 138, and a top strap 122 and a bottom strap 126. The front edges of top strap 122 and bottom strap 126 are shown to be convex, but no center section of the front wall is shown, as set forth in Claim 1.

Further, the back wall 132 of Kaufhold does not have an indented section of reduced thickness, as set forth in claim 1.

Claims 4-12 were rejected over Kaufhold in view of U.S. Patent No. 6,446,820, Barker et al. Barker et al. is relied on as showing a draft gear of resilient material between two coupler followers. However, independent claim 5 sets forth that the front wall of the yoke comprises a bottom section, a center section and a top section each having a laterally convex shape and extending between the two side sections.

Kaufhold discloses a yoke 120 having front side walls 134 and 138, and a top strap 122 and bottom strap 126. The front edges of the top strap 122 and bottom strap 126 are shown to be convex, but no center section of the front wall is shown, as set forth in claim 5.

Further, the back wall 132 of Kaufhold does not have an indented section of reduced thickness, as set forth in claim 5.

It is not understood nor believed supportable how the Examiner can say that a center section of Claims 1 and 5 is a beveled edge in the opening in front of the yoke in Kaufhold. Quite simply, Kaufhold completely lacks the center section of the front wall of the yoke as set forth in claims 1 and 5.

A careful review of Kaufhold reveals the significant structural differences between the presently claimed coupler follower as discussed above.

## 8. Claims Appendix

A copy of claims 1-12, currently under appeal, follows.

1. (original): A yoke for use in a railway locomotive draft gear assembly, the yoke comprising:  
a front wall, a back wall, a top strap extending from the front wall to the back wall,  
a bottom strap extending from the front wall to the back wall,  
the front wall comprising two side sections, each side section extending vertically between the top strap and the bottom strap, the front wall comprising a bottom section, a center section and a top section, each of the bottom, center and the top sections having a convex edge and extending laterally between the two side sections,  
the top strap of reduced width extending from the front wall to the back wall,  
the bottom strap of reduced width extending from the front wall to the back wall,  
and the back wall includes at least one indented section of reduced thickness extending from near the top strap to near the bottom strap.
2. (original): The yoke of claim 1 further comprising,  
an indented area of reduced thickness in the top strap and an indented area of reduced thickness in the bottom strap.
3. (original): The yoke of claim 1,  
where in the back wall includes an inside facing surface forming a bearing area.
4. (original): The yoke of claim 1,  
wherein the width of the top strap is about 8.25 inches,  
the width of the bottom strap is about 8.25 inches  
and the width of the back wall is about 8.25 inches.
5. (original): A draft gear assembly for use in a railway locomotive coupling assembly, the draft gear assembly comprising:  
a yoke comprising:

a front wall, a back wall, a top strap extending from the front wall to the back wall,  
a bottom strap extending from the front wall to the back wall,  
the front wall comprising two side sections, each side section extending vertically  
between the top strap and the bottom strap, the front wall further comprising a  
bottom section, a center section and a top section, each of the bottom, center  
and top sections having a laterally convex shape and extending laterally between  
the two side sections,  
the top strap of reduced width extending from the front wall to the back wall,  
the bottom strap of reduced width extending from the front wall to the back wall,  
and back wall includes at least one indented section of reduced thickness  
extending from near the top strap to near the bottom strap,  
a front coupler follower positioned between the top strap and the bottom strap  
and adjacent an internal surface of the front wall,  
a rear coupler follower positioned between the top strap and the bottom strap  
and adjacent an internal surface of the back wall,  
and a resilient draft gear located between the front and rear coupler followers.

6. (original): The draft gear assembly of claim 5,  
wherein the yoke to strap includes an indented area of reduced thickness,  
and the yoke bottom strap includes an indented area of reduced thickness.

7. (original): The draft gear assembly of claim 5,  
Wherein an inside facing surface of the back wall forms a bearing area.

8. (original): The draft gear assembly of claim 5,  
wherein the width of the top strap is about 8.25 inches,

the width of the bottom strap is about 8.25 inches

and the width of the back wall is about 8.25 inches.

9. (original): The draft gear assembly of claim 5,  
wherein the front coupler follower comprises a generally rectangular structure  
having a top edge, a bottom edge, two laterally spaced side edges, a front face  
and rear face,  
and each side edge having a side support structure extending longitudinally from  
the rear face, each side edge support structure having a lightener opening  
therein.

10. (original): The draft gear assembly of claim 5,  
wherein the front coupler follower comprises a generally rectangular structure  
having a top edge, a bottom edge and two laterally spaced side edges,  
and a center support structure extending longitudinally from the rear face, the  
center support structure having lightener areas at each corner.


11. (original): The draft gear assembly of claim 5,  
wherein the rear coupler follower comprises a generally rectangular structure  
having a top edge, a bottom edge, two laterally spaced side edges, a front face  
and a rear face, and each side edge having a side support structure extending  
longitudinally from the rear face, each side edge support structure having a  
lightener opening therein.

12. (original): The draft gear assembly of claim 5,  
wherein the rear coupler follower comprises a generally rectangular structure  
having a top edge,

a bottom edge and two laterally space side edges,  
and a center support structure extending longitudinally from the rear face, the  
center support structure having lightener areas at each corner.

Reversal of the final rejection and allowance of the claims as appealed is  
respectfully requested.

Respectfully submitted,

By:   
Edward J. Brosius  
Attorney for Applicants  
Reg. No. 28,695

AMSTED Industries Incorporated  
205 North Michigan Avenue  
44<sup>th</sup> Floor  
Chicago, IL 60601  
(312) 819-8482